

**Mulhern Belting, Inc**

Phone: 800-253-6300

Fax: 201-337-6540

Web: <http://www.mulhernbelting.com>Email: [sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)**Part Number: 1-1005****Description: U2W Poli-Glide 5M/2U/BU****Color:** White**Nominal OAG:** 0.060" +/- .015**Plies:** 2**Fabric:** Monofilament**Minimum Pulley Diameter:** Nose Bar**Top Surface:** Smooth Urethane**Bottom Surface:** Bare**Compound:** Urethane**Work Tension:** 50 lbs. PIW**Elongation:** Less than 1%**Weight P.I.W. / Ft.:** .024 lbs.**Working Temperature:** -4F to 180F**FDA Accepted:** Yes**Joining Method:** Finger Splice; Lacing

**Features:** This belt is a lightweight 2 ply monofilament construction that will negotiate small pulleys. The urethane compound is oil, animal fat and grease resistant. It is easy to clean and will lay flat. Refer to the chemical resistance chart when choosing a cleaning solution.

**Applications:** U2W Poli-Glide 5M/2U/BU is used in candy, chocolate and confectionary processing. It is also used in many medium food processing applications such as the cheese, bakery, fish, meat, poultry and vegetable industries.